

## Firmware Features

8-Port GbE/10GbE Micro Switch with PoE+ PSE/PD and optional MACsec



## Feature Specifications

### Provision of Inventory Information

---

- Factory and inventory data
- Custom-defined device information

### System

---

- Integrated thermal protection
- Energy Efficient Ethernet (EEE, IEEE 802.3az)
- Configuration changes
- Alternative MAC address
- LED mode

### IP Stack

---

- Dual stack (IPv4, IPv6)
- DHCP Option 66 / 67
- Ping, traceroute
- Secondary IPv4 address
- Hostname
- DNS

### SFP

---

- SFP DDM (Digital Diagnostic Monitoring)
- MACsec Security Encryption (AES128/AES256) (*MS440407PM-54, MS440417PM-54*)

### Quality of Service (QoS)

---

- 4 priority queues per port
- Prioritization scheme
- Layer 1 priority
- Layer 2 priority (802.1p)
- Layer 3 priority (IPv4 / IPv6)
- Egress rate shaping
- Ingress rate shaping

### Spanning Tree Protocols

---

- Spanning Tree Protocol (STP)
- Rapid Spanning Tree Protocol (RSTP)
- Multiple Spanning Tree Protocol (MSTP)
- BPDU Guard

### Ethernet Port Features

---

- Cable tester
- Loop protection
- Port enable / disable
- Port alias
- Port roles: local, uplink
- Speed negotiation
- Jumbo frame support
- Port mirroring

### PoE Power Management

---

- PoE available maximum power configuration
- PoE enable / disable
- PoE+ PSE enable
- Emergency port

### Switch / MAC

---

- MAC table
- MAC filter
- SNMP access
- MAC limit per port
- Configurable MAC aging time

### RMON Statistics

---

- RMON counters
- Port utilization

### Ring Protocols

---

- MICROSENS Redundant Ring Protocol (MICROSENS Ring)
- Ethernet Ring Protection Switching (ERPS, ITU-T G.8032 v2)

### Multicast (IGMP / MLD Snooping)

---

- IGMP snooping per VLAN
- MLD snooping per VLAN
- IGMP querier
- Static multicast router port

## Feature Specifications (continued)

### Virtual LANs (VLANs)

---

- Port VLANs, tagged VLANs
- Up to 4094 VLANs
- VLAN filter
- Configurable port modes:
  - access
  - hybrid
  - trunk
- Stacked VLANs (Q-in-Q)
- Priority override
- Voice VLAN
- STP / RSTP VLAN
- Unauthorized VLAN
- Management VLAN
- Force port default VID

### Port Access Control

---

- IEEE 802.1X authentication
- IEEE 802.1X supplicant
- RADIUS MAC authentication
- MAC locking
- MAC learning
- Limited number of MAC addresses
- Learned MAC timeout
- Dynamic VLAN
- Wake-on-LAN support
- Network edge authentication
- Authentication fail retry timer

### DHCP

---

- DHCP snooping
- IP-MAC binding table
- DHCP filtering
- DHCP flooding detection
- DHCP relay agent including support for Option 82
- Dynamic ARP inspection

### Command Line Interface (CLI)

---

- Context-sensitive help
- Show device configuration
- Show device status
- Create snapshot
- Live syslog
- Telnet
- Secure Shell (SSH)
- Welcome message

### Login Access Protection

---

- Unlimited number of users
- General access rights
- Disable insecure interfaces
- User permissions
- Public key encrypted passwords
- View model for SNMPv1 / SNMPv2c
- Firewall with black- and whitelist
- Authentication and authorization:
  - TACACS+
  - RADIUS

### Web Interface (WEB)

---

- User authentication
- http(s)
- Custom TLS certificates
- Animated device visualization
- Firmware update
- Online documentation
- SNMP MIB download
- Event display
- RESTful API
- Supported browsers:
  - Google Chrome
  - Mozilla Firefox
  - Microsoft Edge

## Feature Specifications (continued)

### Link Layer Discovery Protocols (LLDP, CDP)

---

- LLDP operation
- LLDP-MED
- CDP operation
- CDP voice VLAN

### Access Control Lists (ACL)

---

- Access control lists (ACL)
- Dynamic ACL via RADIUS

### Link Aggregation Control Protocol (LACP)

---

- Static link aggregation
- Dynamic link aggregation
- Load balancing and trunking

### File Management

---

- File Transfer Protocol (FTP)
- Secure File Transfer Protocol (FTPS)
- FTP server support
- Secure firmware update
- Configuration export and import
- Compare configuration
- Temporary configuration
- Save configuration

### Event Logging

---

- Syslog to CLI
- Local logfile
- Log filters
- Recent logs

### Diagnostic Functions

---

- Ping, traceroute
- Port mirroring
- Test event
- DNS lookup
- LED test
- ARP cache

### Simple Network Management Protocol (SNMP)

---

- SNMPv1 / SNMPv2c
- SNMPv1 / SNMPv2c security
- SNMPv3
- SNMP Transport Security Model (TSM)
- Trap / Inform (SNMPv1 / SNMPv2c / SNMPv3)
- Enterprise-specific notifications
- Enterprise and standard MIBs

### Network Time Protocol (NTP)

---

- NTP client

### Power-over-Ethernet PoE/PoE+

---

- 5x IEEE 802.3af/at PoE+ PSE (max. 30 W)
- 1x IEEE 802.3af/at PoE+ PD(+)
- PoE available max power configuration
- PoE enable/disable
- PoE+ PSE enable
- Emergency port

### Network Management

---

- Support of common management standards
- Software integration with MICROSENS NMP as central management solution for network and device configuration

### Automation

---

- Docker virtualization environment for custom applications

### Miscellaneous

---

- Broadcast storm control

Our General Terms and Conditions of Sale (GTCS) apply to all orders. Please refer to: [https://www.microsens.com/fileadmin/files/downloads/Impressum/MICROSENS\\_AVB\\_EN.pdf](https://www.microsens.com/fileadmin/files/downloads/Impressum/MICROSENS_AVB_EN.pdf)

#### **Disclaimer**

All information in this document is for general information purposes only and is subject to change without notice. MICROSENS GmbH & Co. KG makes no warranty, express or implied, and disclaims any liability for the correctness, completeness or quality of the information provided. MICROSENS GmbH & Co. KG shall not be held liable for any direct, indirect, incidental or consequential damages from the use or misuse of the product or the information contained herein. Any product names mentioned herein may be trademarks and/or registered trademarks of their respective owners.

Document ID: FWF-EN-MS4404-5x7PM-(10)GbE-MicroSwitch-PoE+-opt-MACsec\_v1.0

Date of Issue: 2026-01-29